

N F P A

# Fluid Power

VEHICLE

# Challenge




NFPA  
Education and  
Technology  
Foundation

FINAL PRESENTATION  
Minnesota State University  
Mankato  
Ryan Walerius  
4/16/2024



Twin Cities Engineering  
MINNESOTA STATE UNIVERSITY MANKATO

# Project Outline



# MNSU Team



**Stephan McGruder**  
*Team Lead*



**Jonathan Curillo**  
*Engineer 1*








**Jack Rhodes**  
*Engineer 2*



**Mounkoka Francesca  
Goma**  
*Engineer 3*

# Initial Hydraulic Circuit




- Circuit design utilizes a custom manifold.
- 4 (+1) individual circuits
- Components selected for this circuit earlier in the project
- Circuit design around the sprint race event; Accumulator charging a central focus

# Initial Component Mounting




- Utilizes space between two rear wheels
- Aluminum Extrusion serves as Structural component for mounting
- Reservoir and accumulator surrounding the manifold.



# Pump Gear Box

- Pump Gear Box with a target gear ratio of 15:1 (actual of 14.4)
- Both gears and sprockets were used.
- Estimated 900 rpm at the pump shaft
- Designed to supply ~1GPM to the circuit.



# Motor to Wheel Gear Box



- Motor to wheel gear ratio designed for a 10:1 motor to wheel. Step down.
- Designed for torque to the wheel.
- Utilized using Gears.

# ELECTRONICS



Two electronic control systems

Click PLC


- HDMI
- Two outputs
- 6 modes

Arduino

- Two LCD Screens
- Two outputs
- Reads pressure



# PLC and Ladder logic




	A	B
C1	0	0
C6	0	1
C4	0	1
C5	1	1
C2	1	1
C3	1	1

- C1: Regan
- C2: Sprint
- C3: Endurance
- C4: Efficiency
- C5: Pulse for Efficiency
- C6: Coast

# Pneumatic System

- Circuit to actuate hand valves ball valves within the hydraulic circuit
- Air is pre-charged.
- Valves linked to the hydraulic drive modes.



# Initial Vehicle Components



- Gears boxes
- Accumulator
- Electronics
- Manifold
- Pneumatic system
- Reservoir

# Vehicle Testing



- Motor testing
  - Adequate flow and pressure
- Manifold testing
  - Adequate pressure and flow.
  - Correct routing
  - Valves working properly.
- Pump testing
  - Pedaling resistance.
  - Leaks and correct flow.
  - Correct spin orientation.
- Gearbox testing
  - Correct meshing of gears.
  - Correct orientation.







# Critical Juncture



- Motor deemed inoperable due to not spinning under hydraulic pressure.
- Test conducted
  - Bench tested the motor.
  - Ensured proper assembly of motor with correct tolerances.
- Resulted in swapping motor for a known working one

# Current Hydraulic Circuit



# Vehicle (Bike) Building




- **Changes**
  - Removed Manifold and inoperable motor.
  - Swapped motor from 0.25 CiD to 1.27CiD
  - Changed gear ratio for both the Pedals and the motor to align with the new motor.
  - Added hydraulic hand pump and a duplicate pneumatic valve circuit


# Current Vehicle Iteration



Hand pump replacing  
the manifold



Wooden bumper  
(Wumper)



Rerouted accumulator  
hoses and analog  
pressure gauge



# Lessons Learned


- Design conception
- Gear ratio/gear box
- Pressure readings
- Leaks and fittings
- Time management
- Flexibility in with design changes
- Resource management

# Acknowledgements



- We would like to express our sincere gratitude to Ernie Parker, Tony Hennum, and Fred Wlizlo for their invaluable guidance and support throughout the preparation of this project and presentation. Their expertise and encouragement have been instrumental in shaping the outcome of our project.

# Special Thanks to:



NFPA  
Education and  
Technology  
Foundation



An APPLIED Fluid Power® company





# Questions?

