

# Report and Design Presentation

## Chainless Challenge 2015/2016 - WMU



### Mechanical Team

Andrew Bonter  
Cameron Brown  
Aaron Huntoon  
Austin Vojcek

### Electrical Team

Dex Naranjo  
Luis Placido  
Mojtaba Al Jaffar


### Faculty Advisors

Dr. Alamgir Choudhury  
Dr. Jorge Rodriguez

# Overview

- Project Plan/ Objectives
- Design Analysis and Drawings
  - Mechanical
  - Electrical
- Actual Test Data
- Cost Analysis
- Lessons Learned and Conclusions

# Project Planning



# Objectives - Mechanical

**Design, fabricate, and test a unique human-assisted hydraulic system**

- Create a system to meet regulations/objectives
- Include green engineering and sustainable process
- Minimize cost of competition vehicle
- Innovate from previous years' designs

# Evaluation Criteria

## **Safety/Reliability**

- Maintain safe operating pressure
- All components safely mounted

## **Innovation**

- Utilize different hydraulic components

## **Manufacturability**

- Ease of assembly and fabrication

## **Cost**

- Lowest cost that satisfies objectives

## **Marketability**


- Customer-focus on unique design

# Design Analysis

## **Design Concepts**

- Power Transmission System
  - Hydraulic fluid was the selected medium
- Vehicle Type
  - Research conducted on multiple frame types
- Brainstorming Ideas
  - Reservoir placement optimization
  - Frame extension
  - Aerodynamic shell
  - Electrical control system
  - Hub utilization

# Hydraulic System



# Frame Design

- Factors weighted on importance – scores averaged
- Frame extension
- Criteria:
  - Weight
  - Aerodynamics
  - Mounting Area
  - Adaptability
  - Etc. (see matrix)





# Frame Decision (Upright Bicycle)

		<b>Upright</b>	<b>Tricycle</b>	<b>Recumbent</b>
<b>Factors</b>	<b>Weight Factor</b>	<b>Average</b>	<b>Average</b>	<b>Average</b>
<b>Safety</b>	14	6	7	7
<b>Weight</b>	13	9	3	5
<b>Adaptability</b>	12	5	8	5
<b>Mounting Area</b>	11	5	8	5
<b>Maintenance</b>	10	8	6	5
<b>Operability</b>	9	7	7	3
<b>Cost</b>	8	8	5	3
<b>Stability</b>	7	6	8	9
<b>Load Limit</b>	6	5	8	7
<b>Drag</b>	5	7	3	7
<b>Maneuverability</b>	4	8	5	5
<b>Climbing</b>	3	4	7	6
<b>Rider Comfort</b>	2	7	6	9
<b>Aesthetics</b>	1	9	3	6
	<b>Total Score:</b>	<b>668</b>	<b>630</b>	<b>577</b>

# Pumps and Motors

## Criteria:

- Safe for Mounting
- Weight
- Efficiency
- Displacement & Flow Rate
- Dimensions
- Cost



# Pump/Motor Analysis

Pumps	Flow Rate out	Hydraulic HP	Volume Occupied	Total Efficiency @ 500 RPM	Weight	Displacement volume	Cost
<b>F 11-5 P@800</b>	2206.9 CC/m	0.271	83.66 in <sup>3</sup>	90.4%	11 lbs	4.9CC/rev	\$600
<b>F 11-10 P@400</b>	4315.3 CC/m	0.265	118.13 in <sup>3</sup>	88.4%	16.5 lbs	9.8CC/rev	\$715
<b>AM1C-31</b>	2558.9 CC/m	0.252	38.25 in <sup>3</sup>	84% @ 600 RPM	4 lbs	5.1 CC/rev	\$800
<b>PGP505 P@800</b>	2270.58 CC/m	0.234	34 in <sup>3</sup>	78%	5.26 lbs	6CC/rev	\$250

**\* H3 Eliminated due to space occupied by the pump**

# Accumulators

## Criteria

- Capacity
- Energy Density
- Dimensions
- Weight
- Cost




# Accumulator Analysis & Data

<b>Parker Accumulators</b>	Price (\$)	Gal	Weight (lb)	Weight (w/ oil) lbs	PSI	Dims.	<b>Energy Density (ft-lb)/lb</b>
BA005B3T01A1	\$704.00	0.65	16	20.98	3000	ø4" x 15"	1786.45
AD280B25T9A1	\$672.00	0.74	21	26.68	3600	Ø6.75" x 9.5"	1922.11
BA01B3T01A1	\$374.57	1	34	41.68	3000	ø6.75" x 17"	1385.56
T0BUL4.5AL-20	\$850	1.08	20	28.29	3000	ø4" x 24"	2204.67

# Valves, Ports and Connections

- 3-way flow control valves (4)
- Variable flow control valve (controlling accumulator pressure release) (1)
- Braided Stainless Steel lines (18ft)
- 2.5 Gallon Rigid Reservoir (1)



# Gearing and Hubs

## Gearing to Pump

- Highest input ratio: 1 to 11.62
- Lowest input ratio: 1 to 3.791

## Motor to Wheel

- Highest output ratio: 1 to 1
- Lowest output ratio: 1 to .625

## Hubs

- Front Hub: Shimano Alfine SG-S501
- Rear hub: Strumey Archer S3X



# Objectives - Control System

Design and build an electronic control system to reconfigure the hydraulic circuit for all modes of operation through a simple user interface.

The system also should:

- Provide visual feedback on the status of the hydraulic circuit.
- Set efficient flow parameters for flow release from accumulators.
- Contribute to enforcing safety.



# Design Criteria

## Intuitive and Simple User Interface

- User commands issued by pressing on pushbuttons.
- Use as few pushbuttons as possible to cover all the control functions.
- Choose appropriate placement to support functionality.

## Real-Time System Feedback

- Include graphical display to show vehicle speed, hydraulic pressures, current operation mode, and alarms in real time.

# Design Criteria

## Modular Design

- Control system to be developed in separate modules with specific functions to streamline prototyping, testing, and final assembly.
- Add flexibility for spatial distribution relative to other system components.



## Low Cost

- Achieve lowest cost that satisfies the objectives.

# System Components

## Control Panel:


- STM32F4 Discovery microcontroller board
- LCD graphic display  $\mu$ LCD-43PT
- Custom-made interface board
- Connector headers for peripherals
- Push and toggle buttons
- Rigid enclosure



# System Components

## Power Control Box:

- PWM solenoid-driver circuits
- Linear voltage-controlled current source circuit
- Linear voltage isolator circuits
- Rigid enclosure



# System Components

## μLCD-43PT Display Code:

- 4D Graphics Language – Developed with 4D Workshop 4
- Generates, displays, and animates graphic elements

## STM32F4 Discovery Microcontroller Code:

- C Language – Developed with IAR Embedded Workbench
- Processes user input to implement logic for hydraulic operation modes
- Calculates and displays sensor data
- Controls all other components in the system

# Final Product and Testing

- Upon completion the final bike weight was about 168 pounds, including hydraulic fluid
- Functional testing was done on campus

## Testing included:

- Direct Drive
- Accumulator charging time
- Efficiency testing
- Electrical control testing
- Sprint testing
- Endurance testing



# Design Drawings


- CAD and Bracket Analysis
- CAD Models
  - Handlebars, pushbuttons, and display screen
  - Rear mounting plate and components
  - Front hub, pump mount, and gear train
  - Completed bike (including manikin)

# Handlebars, pushbuttons, display






# Rear mounting plate and components



Creo Parametric - Advanced Rendering Extension


# Front hub, pump mount, and gear train




# Completed Bike




# Finite Element Analysis



# Finite Element Analysis



# Finite Element Analysis



# Finite Element Analysis

## Final Design


### Material of Brackets

- (Connecting to frame)  
Steel
- (Accumulator rest,  
Component Plate)  
Aluminum


### Yield Strength

- (Steel 1040) 415 MPa
- (Aluminum 2014-O)  
414 MPa

Source: Mott R., (2014) Machine Elements in Mechanical Design, Fifth Ed.





# Finite Element Analysis





# Finite Element Analysis



# Cost Analysis (500 units)

Subsystem	Description	Part Cost	Labor Cost	Quantity Discount	New Part Cost	New Labor Cost
Hydraulic Components	Pumps/Motors, Accumulators, Hand pump, Reservoir	\$3,573.96	\$0.00	Bulk discount: 25%	\$2,680.47	\$0.00
Valves	Pressure relief valve, check valve, proportional valve, directional control valve	\$757.64	\$0.00	Bulk discount: 25%	\$568.23	\$0.00
Bicycle Components	Bicycle frame	\$478.99	\$0.00	Bulk discount: 30%	\$335.29	\$0.00
Hydraulic Connections	Hose, fittings, adapters	\$730.47	\$0.00	Bulk discount: 30%	\$511.33	\$0.00
Gear Train	Front hub, rear hub, misc. gears	\$665.22	\$90.00	Bulk discount: 20%	\$532.18	\$0.00
Electronics	Control panel, power box, etc.	\$250.98	\$0.00	Bulk discount: 40%	\$150.59	\$0.00
Fabrication	misc. materials, aluminum and steel	\$181.12	\$1,770.00	Bulk discount: 35%	\$117.73	\$885.00
Misc. materials	bolts, nuts, screws	\$88.43	\$0.00	Bulk discount: 50%	\$44.22	\$0.00
<b>Cost of Parts and Materials</b>		<b>\$6,726.81</b>			<b>\$4,940.03</b>	
Cost of labor	Parts preparation		\$1,860.00			\$885.00
Cost of labor	Assembly		\$360.00		Jig/fixture assembly and set up	\$120.00
<b>Total Cost</b>			<b>\$8,946.81</b>			<b>\$5,945.03</b>
<b>Percent Reduction</b>						<b>33.55%</b>
<b>Total Cost (500 units)</b>						<b>\$2,972,514.50</b>

# Pump and Motor Testing

- Testing conducted at Parker Aerospace
- Due to nature of their business, unable to retain hard data
- Information learned on the function of our pump/motor:
  - For our application they have the ability to flow either direction
  - Case drain not needed

# Accumulator Testing and Trial Runs

- One accumulator tested at a time – isolate any issues and reduce number of variables
  - First 2 runs = horizontal accumulator
  - Third run = angled accumulator
- Runs made in building (400m in length)
- Nitrogen pre-charge of 500 psi

# Accumulator Testing and Trial Runs

- One final run with both accumulators in use was made outdoors – bike traveled  $\frac{1}{2}$  mile ( $\sim 800$  meters)

Run #1		Run #2		Run #3	
Distance (m)	PSI	Distance (m)	PSI	Distance (m)	PSI
0	2600	0	2600	0	2600
10	1600	10	1650	10	1620
100	1330	100	1350	100	1340
150	1150	150	1170	150	1160
200	900	200	910	200	900
300	810	300	810	300	810
400	720	400	720	400	720

# Post-Race Notes

- Bike arrived damaged – flat tire
- Parts of the hydraulic circuit malfunctioned before the efficiency race – adapt circuit to isolate section



# Lessons Learned and Conclusions

- Design refinement cycle
  - Test, analyze, improve, repeat
- Project planning and time management
- Have rational and reasoning behind every decision
- More background knowledge on major components needed

# Questions?

We want to thank you for your time from  
the WMU 2015-2016 Chainless  
Challenge Team

**Go Broncos!!**